



FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO PUBLIC.

**UNDERBODY** Protective insulator based on bituminous catramine. Ideal for protection from abrasion to exposed auto body parts. It is resistant to the atmospheric agents. Suitable product for every kind of plastic and does not require primer.



## **Technical Specifications:**

Quantity	400 ml
Barcode	8034108893730
Aspect	Tin-Plate can containing under pressure fluid
Chemical base	Bituminous with solvents
Color	Black
Odour	Typical of solvent
Relative density	at 20°C (68 °F) 0,80 ÷ 0,84 g/ml
Flash point	< 0° C (32 °F) extremely flammable
Pressure	at 20°C (68 °F) 5,5 ± 0,5 bar
Viscosity	> 15" Coppa Ford
Thickness	As necessary
Resistance temperature	-10°C / +100°C (14 F / 212 F)
Drying time T=20°C:	Out dust 10 minutes
	Dry to touch 30 minutes
	Dry in depth 24 hours
Other informations	Not overcoatable
	Cleaning: solvent (wet), mechanical (dry)

FIELDS OF APPLICATION

metal or plastic lower part of cars or wheel arches of all kind of vehicles.

**HOW TO USE:** - Vigorously shake the can for at least 1 minute, until you hear the inner marbles move freely. It is also suggested to occasionally shake the cylinder even during use; - Carefully clean the surface before application; - Test in a hidden area to verify compatibility of the surface with the paint. - Apply a first hand / coat light to improve coverage and adherence, to reduce the possibility of dropping. Apply from a distance of 20-30 cm; - After a few moments apply a second horizontal hand/coat immediately followed by a third vertical hand / coat; - Let dry a few minutes; - After use, it's advisable to spray for 2/3 seconds with the spray upside down, to avoid the block of the actuator; - After 24h, proceed with the normal use of painted piece.

## MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

## BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT



Ambro-Sol - 25020 Cigole (BS) Italy www.ambro-sol.com - info@ambro-sol.com