



## Lithium Multipurpose Grease 200 ml (G009)

This grease is perfect for the everyday use. It's ideal for your car but also for industrial uses: it has many excellent features, in particular the resistance from water and atmospheric agents.



Quantity	200 ml
Barcode	EAN 13: 8034108891613
Box / Case	12 pz

**LITHIUM MULTIPURPOSE GREASE** – A compound of high quality saponified greases. This grease has a wide range of uses and good chemical stability. It is water-repellent and has adhesive properties. It protects against water and it is perfectly stable and resistant to salty and dirty atmospheres, acid and basic solution and atmospheric corrosion. Ideal for lubricating, bearing, bushes, hubs, kingpins, guides and general use on motor vehicles, farming and industrial machinery.

### Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	Light brown
Odour	Characteristic of solvent
Relative density	at 20°C 0,61 ÷ 0,65 g/ml
Flash point	Und. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Consistency	NLGI EP2 (soap of lithium base)
Penetration	265-295 at 25°C 0.1 mm
Drip point	+ 180°C
Application temperature	-40°C - +170°C

**HOW TO USE:** shake and spray directly on the surface from a distance of 15-25 cm. The product could be also be used with a straw that is attached to the cap.

### MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

**BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT**