



Stringy Adhesive Grease for chains HQ (G012)

High performance chain grease. This high quality product developed and tested for the racing industry (on-and off-road motorcycles) provides guaranteed lubrication for extended periods of intense use.



Quantity	400 ml
Barcode	EAN 13: 8034108892405
Box / Case	12 pz

STRINGY ADHESIVE GREASE FOR CHAINS HQ – High performance chain grease, this high quality product developed and tested for the racing industry (on-and off-road motorcycles) provides guaranteed lubrication for extended periods of intense use. It penetrates and lubricates links and pins to ensure elevated output and precision; it constantly guarantees the highest performance of the transmission mechanical elements. It reduces wearing of chains, crowns, pinions and all mechanical moving parts, while also protecting against water and dust.

Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	Dark brown
Odour	Characteristic of solvent
Relative density	at 20°C 0,71 ÷ 0,75 g/ml
Flash point	Und. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Viscosity at 100°	(cSt) 2500-3000
Penetration at 25°	265-295
Application temperature	-40°C - +200°C (peak)
Solubility	insoluble

HOW TO USE: shake and spray directly on the surface from a distance of 15-25 cm. The product could be also be used with a straw that is attached to the cap.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT