



Nautical Lithium Grease 1 Lt (G014)

This big jar of lubricant contains lithium and titanium oxides that make it specific and suitable for the nautical sector. It resists at oxidation and at aggressive atmospheric agents. It operates with high temperature and with low temperature.

Quantity	900 g
Barcode	EAN 13: 8034108892603
Box / case	8 pz



NAUTICAL LITHIUM GREASE – This grease contains lithium and titanium oxides that make is specific and particularly suitable for the nautical sector. It has excellent long-term lubrication and performs in the presence of saline and aggressive atmospheres. It has long-term stability and resistance to oxidation. It protects surfaces from corrosive agents and it's perfectly suitable for both high temperatures (220°C/428°F) and low temperatures (-40°C/-40°F). Excellent for lubricating pins, joints, transmissions, levers, suspensions, hinges and exposed machine parts on outboard motors and boats.

Technical Specifications:

Aspect	Metal jar
Color	Creamy white
Odour	Odourless
Relative density	at 20°C 0,93 g/ml
Flash point	> 240° C
Solubility	Insoluble in water
Consistency	NLGI EP2
Penetration at 25°C 0.1 mm	265 - 295
Drip point	+ 190 °C
Application temperature	- 40°C - + 220°C

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT



Ambro-Sol - 25020 Cigole (BS) Italy - www.ambro-sol.com - info@ambro-sol.com