





Vaseline Grease 1 Lt (G015)

Highly pure grease designed for uses that require periodic maintenance, cleaning and lubrication. This Ambro-Sol product is excellent for lubricating delicate mechanisms.

A description of the control of the	SALA WAZELINGWY	R: CHING WITH A COMMITTED TO THE PROPERTY OF T

Quantity	900 g
Barcode	EAN 13: 8034108892610
Box / case	8 pz

VASELINE GREASE – Highly pure grease designed for uses that require periodic maintenance, cleaning, and lubrication. Excellent for lubricating delicate mechanisms. Its good stability guarantees long-term protective, lubricating and anti-acid action. It does not harden overtime. It can also be used to protect electric components (terminals and connectors).

Technical Specifications:

Aspect	Metal jar
Color	white
Odour	Odourless
Relative density	at 20°C 0,88 ÷ 0,92 g/ml
Flash point	+210° C
Solubility	insoluble in water
Penetration at 25°C 0.1 mm	n.l. ASTM D 937 mm/10 160 ÷ 200
Drip point	ASTM D 127 °C 52 ÷ 60
Viscosity at 100°C	mm2/s 6,5 ÷ 8
Kinematic viscosity	5 – 9 mm2/s (100°C)

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT



Ambro-Sol - 25020 Cigole (BS) Italy - www.ambro-sol.com - info@ambro-sol.com