



Copper Grease 1 Lt (G017)

This version is ideal for professional uses, for example in steel factories and iron and steel industries. This product operates at high temperature (until 1.000°) and it has a deep protective action: the corrosion won't be a problem!

Quantity	900 g
Barcode	EAN 13: 8034108892634
Box / Case	8 pz

COPPER GREASE – This product is made of super fine foliated copper particles and special corrosion inhibitors. It has protective and lubricating properties at high temperatures. High temperature resistance to 1000 °C/1832°F. High adhesive capacity and anti-corrosion capacity make it ideal for all cases where heat or a highly corrosive environment can create irreversible blocks: slip, ring, pins, motor, exhausts, electrical, contacts, threaded connections, injection valves, etc.



Technical Specifications:

Aspect	Metal jar
Color	copper
Odour	Odorless
Relative density	at 20°C 0,88 ÷ 0,92 g/ml
Flash point	> 280° C
Solubility	Insoluble in water
Consistence	NLGI EP 2
Penetration at 25°C 0.1 mm	265 - 295 mm/10
Drip point	ASTM D566 infusibile
Application temperature	-40 °C - 1000°C/1100 °C (peak)

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT