





Silicon Grease 125 ml (G022)

Tube version for this excellent Ambro-Sol lubricant with different features: it's water-repellent, isolating, polish and protective. It also operates against oxide and it removes all plastic adhesive materials.



Quantity	125 ml
Barcode	EAN 13: 8034108898841
Box / Case	12 pz / 24 pz / 48 pz

SILICON GREASE – This grease is colorless and odorless due to its methyl siloxane base (silicon oil). It provides excellent lubricating, insulating and protective action on many different materials. It protects surfaces from corrosion caused by vapors and smoke. It can be used as water repellent on fabrics on many types of fabric and leather. It will maintain long-term elasticity of rubber parts (ex: O- rings, seals). This product can also be applied as a polisher and protector on metal surfaces. When spread with a cloth on steel, copper, bronze, brass or silver it will prevent rust and keep surfaces clean and glossy for long periods.

Technical Specifications:

Aspect	Tube
Color	pale white
Odour	Odourless
Relative density	at 20°C 0,88 ÷ 0,92 g/ml
Flash point	>300° C
Consistency	220 - 250 mm/10
Penetration at 25°C 0.1 mm	190 ÷ 240
Drip point	+ 200 °C
Application temperature	- 55°C - + 220°C
Pour point	< - 10°C

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT



Ambro-Sol - 25020 Cigole (BS) Italy - www.ambro-sol.com - info@ambro-sol.com