

Molybdenum bisulfide Grease 125 ml MOS2 (G023)

"Smart" version, very comfortable for professional or home use. This lubricating grease is able, for its own intrinsic characteristics, to tie itself to the metals also under the worst conditions.

Quantity	125 ml
Barcode	EAN 13: 8034108898858
Box / Case	12 pz / 24 pz / 48 pz



MOLYBDENUM BISULFIDE GREASE – This superior classic black grease stands out because of its adhesiveness to metals in the most difficult conditions. It is high temperature resistant (300°C/572°F). It features extraordinary mechanical stability and provides excellent protection against oxidation, humidity and corrosion. It is ideal for lubricating both standard and high-load bearings.

Technical Specifications:

Aspect	Tube
Color	Black
Odour	characteristic
Relative density	at 20°C 0,88 ÷ 0,92 g/ml
Flash point	>200° C
Solubility	Insoluble in water
Consistence	NLGI EP 2
Penetration at 25°C 0.1 mm	265 - 295 mm/10
Drip point	> 270°C
Application temperature	-20°C - 300°C (peak)
Wheel Bearing test	(3 hour at 80°C) < 10 %

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT