



## Ceramic Grease 400 ml (G024)

Grease with special properties, this ideal lubricant is suitable for situations where high temperatures are present: it withstands up to 1200°C, avoiding unpleasant episodes of blocking.



**HOW TO USE:** shake and spray directly on the surface from a distance of 15-25 cm. The product could be also be used with a straw that is attached to the cap.

Quantity	400 ml
Barcode	EAN 13: 8034108894553
Box / Case	12 pcs

**CERAMIC GREASE** - Ceramic-based grease which applies mostly on parts exposed to high pressure or very high temperature (1200°C/2192°F). It possesses a high lubricating and anticorrosive power, that protects from moisture. This ceramic-based and metal-free spray eliminates squeaking and creaking. Suitable for ABS and ASR brakes, oxygen sensors, and brake parts in general.

### Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	white
Odour	Typical of solvent
Relative density	at 20°C 0,64 ÷ 0,68 g/ml
Flash point	Und. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Consistency	NLGI EP 2
Penetration at 25°C	300 - 305 mm/10
Dripping point	>300°C ASTM D566
Application temperature	-40 °C - 1200°C/1500 °C (peaks, on dry residual without air contact)

### MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

**BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT**