



Paint Remover 750 ml (I262)

This paint remover is ideal for industrial use, for professional use and for DIY. It can be used on different materials, it removes all type of paint. It leaves the treated part clean and without residuals.



Quantity	750 ml
Barcode	EAN 13: 8034108892580
Box / Case	12 pz

PAINT REMOVER – It quickly removes all types of paint from metal and wood surfaces as well as other materials such as glass, polyethylene, and polypropylene. It prepares the worked part for a new treatment leaving it clean and free of residue. Caution: It may have damaging results on some pre-painted surface.

Technical Specifications:

Aspect	Tin-Plate Can
Colour	Whitish
Odour	Characteristic of solvent
Relative density	0,885 kg/l at 20°C
Flash point	Und. 0° C extremely flammable
Initial boiling point	> 35°C
boiling range	+64 / +210 °C
Vapor Density	> 1
Stringiness	3000-4500 cP
Solubility	Water insoluble
Free from chlorinated solvents	Contains DMC

HOW TO USE: Mix the product after the opening of the can. Apply a thick layer of paint remover with a hard brush or a spatula. Wait for the total penetration of the product after remove it all with a spatula or with a rag. It has a high thixotropy also for application on vertical surfaces. Avoid the use on hot surfaces or exposed to sunlight. In case of use on wood, since the support is natural and variable, it is advisable to do an application test, in a small inconspicuous area to avoid problems.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT