





Transparent Plastic Coating (I270)

Transparent plastic coating, which protects against oxidation and corrosion due to weather conditions. It forms an invisible and flexible film ideal for protecting metals such as copper, silver, aluminum and bronze. It also protects other materials such as paper, stone, wood and plastic. It does not yellow over time.



HOW TO USE: Clean the surface to be treated with synthetic thinner. Turn the bottle and shake well until the marbles move freely inside the cylinder. Test spray once or twice and proceed with the application intended. To prevent dripping, apply two thin coats from a distance of 20-30 cm.

TRANSPARENT PLASTIC COATING – This is a protective and invisible paint that protects against rusting and corrosive effects of weathering. It does not yellow over time. It forms a flexible film used for metals such as silver, copper, bronze, aluminum, and protects wood, plastic, stone, and paper.

Technical Specifications:

Quantity	400 ml
Barcode	EAN 13: 8034108893655
Box / Case	12 pcs
Aspect	Tin-Plate can containing under pressure fluid
Color	Transparent
Odour	Typical of solvent
Relative density	at 20°C 0,71 ÷ 0,75 g/ml
Flash point	Less than 0° C extremely flammable
Pressure at 20°C	4/6 bar4/6 bar
Dry residue	About 6%
Brilliance	About 90 gloss
Thickness	About 9 micron
Suitable materials	wood, metal, iron, aluminum, steel, glass,
	plastics, paper materials.
Operating temperature	-10°C / +100°C (Peaks 120° C)
Drying times	Out of dust 10 minutes
	Dry on touch 15 minutes
	Dry on depth 22 hours

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT



Ambro-Sol - 25020 Cigole (BS) Italy - www.ambro-sol.com - info@ambro-sol.com - <a h