



PTFE Lubricant (L050)

Do you need a spray to lubricate parts under strong pressure? Then this Ambro-Sol product is for you! It prevents freezing and corrosion, it removes creaks and it prevents short circuit and malfunctioning.



HOW TO USE: shake and spray directly on the surface from a distance of 15-25 cm. The product could be also be used with a straw that is attached to the cap.

Quantity	400 ml
Barcode	EAN 13: 8034108890081
Box / Case	12 pz

PTFE LUBRICANT – It creates a lubricating transparent film that prevents dirt from depositing. Particularly suited for the lubrication of parts subjected to high pressure. It prevents rubber parts from freezing and corrosion by salt water. It prevents short-circuits and malfunctions caused by humidity in electrical conductors. It eliminates squeaking, water repellent, and silicone-free. It also facilitates the insertion of cables and cords inside sheathes. Commonly used for the maintenance of tools, gaskets and seals, door hinges and locks. High temperature resistant (250°C/482°F).

Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	Light white
Odour	Characteristic of solvent
Relative density	at 20°C 0,62 ÷ 0,66 g/ml
Flash point	Und. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Melting point	ASTM D4591 deg C 334,70
PTFE Aver. particle size	INTERN micron 3,0 +/- 2
Specific gravity	ASTM D4894 g/cm ³ 2,18 +/- 0,05
Melting point PTFE	327°C \cap 340 °C
Maximum temperature	400°C (peaks)

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT