

# Waterproofing leak seal 500 ml (M203)

A filler and spray paint that can be used on irregular surfaces in masonry, asphalt, wood and many other surfaces. Ambro-Sol has always a stop-gap solution!



**WATERPROOFING LEAK SEAL** – Filler spray suitable on irregular surfaces such as walling, asphalt, masonry, wood and many more. It allows the sealing of holes and cracks, preventing water, moisture and rusting. The final result will be a smooth surface ready to be painted.

## **Technical Specifications:**

Quantity	500 ml
Box / Case	12 Pcs
Aspect	Tin-Plate can containing under pressure fluid
Color	transparent, black, white
Odor	Typical of solvent
Relative density	at 20°C 0,78 ÷ 0.82 g/ml
Flash point	< 0° C/ 32 °F extremely flammable
Resin	Synthetic
Solvent	Organic
Dry residual	18% - 20%
Application Temperature	10 - 32 °C – 50°/ 90 °F
Umidity	< 85 %
Pressure at 20°C	4/6 bar
Drying times 20°C	Dry on touch: 45 minutes
	Full Drying (to over paint): 24 hours

#### HOW TO USE

Shake vigorously the can for at least 1 minute until you hear the inner marbles move freely. Shake even during use. Remove dirt and, if possible, any pre-existing paint. Do not apply on hot surfaces (> 90°C/ 194°F). Use outside or in a well-ventilated area. Keep a distance of 20 - 30 cm/8 - 12 inches during spraying.

#### APPLICATION

Apply a first light layer and a second layer at least 45 minutes apart from each other. Depending on the depth and size of the slot / hole, it is possible to apply the product close to the surface to obtain a better filling effect. It is recommended to use on an inclined and / or flat surface. The product may form foam and / or bubbles. You can re-apply after 24 hours of drying. When finished, turn the bottle over and spray until the product is completely drained to clean the dispenser.

### MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 5°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT



Ambro-Sol - 25020 Cigole (BS) Italy - www.ambro-sol.com - info@ambro-sol.com