



Cutting Oil 600 ml (OL109)

This Ambro-Sol spray is ideal for hard metal cutting and operations. It's perfect for hydraulic and steel sectors.



HOW TO USE: shake and spray directly on the surface from a distance of 15-25 cm. The product could be also be used with a straw that is attached to the cap.

MODALITY OF STORAGE

Before using: stock the product in a dry location and don't stock it with a temperature under 0°C and over 45°C, after the use, keep containers closed. In the original package, the product can be conserved for 24 months (warranty). The product doesn't expire.

After the first usage: conserve in a fresh and dry location, away from hot spring. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

Quantity	600 ml
Barcode	EAN 13: 8034108892320
Box / Case	12 pz

CUTTING OIL - HEAVY-DUTY PROTECTIVE TOOL LUBRICANT -
New product developed for specific professional applications in hard metal cutting operations. This oil has a paraffin mineral base, enriched with special EP anti-weld additives. Ideal for use in difficult threading operations with particularly hard, alloy steel. Suited for use in the hydraulic sector.

Technical Specifications:

Aspect	Tin-Plate can containing under pressure fluid
Color	Light brown
Odour	Characteristic of solvent
Relative density	at 20°C 0,64 ÷ 0,68 g/ml
Flash point	Und. 0° C extremely flammable
Pressure at 20°C	4/6 bar
Pour point	< - 10°C
Viscosity Oil at 40°C	288 - 352 cst
Max temperature	>300°C (Oil Content)
Initial boiling point	>250°C (at atmospheric pressure)

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT